

SUPREME TANDEM ROLLED BODIES

EXTRA FEATURES INCLUDED

- **Rocker Roller Springs**
- **Tube Holders in each corner with Deflection Rails**
- **Sand Blasted prior to painting**
- **2 Pack Under Coated**
- **Top Coated in Our Standard Colours**

STANDARD FEATURES

- Rolled C/Plate floor with 350mm High Side
- Front & rear opening tailgates with tie rails
- C/Plate Tailgates & Mudguards
- Full length side tie rails with Deflection Rails
- Swing handles to secure the tailgates
- V- type draw bar made from square RHS tube
- Spare Wheel Holder on Draw Bar
- Lockable plunger coupling
- LED ADR approved lights and reflectors/ Light protectors
- Mudflaps to comply with Australian standards
- New wheels **(NOTE NOT SECOND HAND)**
- Plug holder fitted on draw bar
- Mechanical disk brakes /Cable hand brake fitted
- Tube holders in each corner for fitting cage or H/frame



SPECIFICATIONS

BODY/FLOOR	350MM Sides 2 piece 2.1mm Rolled Checker Plate Tub
TAILGATES	2.1mm Folded Checker Plate, with tie rails
MUDGARD	2.1mm Checker Plate, 250mm Wide 4 Fold
DEFLECTION RAILS	50x50 Angle on each side
SIDE TIE RAILS	27x2mm Pipe Round Full Length (extra reinforced)
COUPLING	50mm Mechanical over Ride Plunger Type / Hand Brake
SUSPENSION	Rocker Roller Load Sharing Springs
AXLES/BRAKES	40mm Square Solid/ Mechanical Disc
BRAKES	Mechanical Disc/Galvanised Calliper's True Cable Hand Brake
HUBS/FORD	LM A-type PCD 114.3, 5 x 1/2" Studs (Stud Centre 66.6mm)
BEARINGS	Bearing A-type Inner Large LM67048 Outer Small LM11949
RIMS	NEW Sunraysia Type 14x5.5" CB 84mm PCD 114.3 (FORD)
TYRES	NEW 185R14C
CHASSIS	ALL 50x50 RHS
DRAW BAR	100x50x3mm RHS V-type, with spare wheel holder
SAFETY CHAIN	10mm Rated chain 450mm Long
LIGHTS	LED Multi volt 12-24v, With Side Clearance Lights 7-Pin plug

<u>TRAILER DIMENSIONS</u>			<u>TRAILER PRICES INCLUDE GST</u>		
	8x5	10x5	Trailer	8x5	10x5
SIDE HEIGHT	350	350	TRAILER		
FLOOR HEIGHT	530	530	Spare		
OVERAL HEIGHT	880	880	J/wheel		
INSIDE LENGTH	2440	3050	Rego		
INSIDE WIDTH	1520	1520	Cage		
DRAWBAR LENGTH	1500	1500	Ramp		
OVERAL LENGTH	3990	4600	H/frame		
OVERAL WIDTH	2030	2030			
LOAD RATING KG	2000	2000			
ATM KG	460	500			
PAYLOAD KG	1540	1500	Total		

Contract _____

NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION