



12 Sherriffs Rd West
Lonsdale, SA 5160
Factory & Sales
P: (08) 8326 5041
F: (08) 8326 7128
www.moderntailers.com.au

1 Levels Court
Pooraka, SA 5095
Sales
P: (08) 8262 2562
F: (08) 8260 7366
E: sales@moderntailers.com.au

SUPREME ROLLED BODY TRAILERS

EXTRA FEATURES INCLUDED

- **FLOATING SHACKLE SPRINGS**
- **TUBE HOLDERS IN EACH CORNER**
- **SAND BLASTING PRIOR TO PAINTING**
- **UNDERCOATED WITH 2 PACK**
- **TOP COATED IN OUR STANDARD COLOURS**

STANDARD FEATURES

- **Rolled C/Plate floor and body 350mm high sides**
- **Front & rear opening checker plate tailgates with tie rails**
- **Mudguards checker plate with deflection rails**
- **Swing handles to secure the tailgates**
- **V- type draw bar made from square RHS tube**
- **Spare wheel holder on draw bar**
- **Lockable plunger coupling**
- **LED ADR approved lights (Protected) front and side reflectors**
- **Mudflaps to comply with Australian standards**
- **New wheels (NOTE NOT SECOND HAND)**
- **Plug holder welded to the draw bar**
- **Tube holders in each corner for fitting cage or H/frame**



SPECIFICATIONS

BODY/FLOOR	350MM Sides 2 piece 2.1mm Rolled Checker Plate Tub
TAILGATES	2.1mm Rolled Checker Plate, with tie rails
MUDGARD	2.1mm Checker Plate, 250mm Wide 4 Fold
DEFLECTION RAILS	50x50 Angle on each side
SIDE TIE RAILS	27x2mm Pipe Round Full Length (extra reinforced)
COUPLING	50mm Lockable Plunger
SUSPENSION	<i>Floating Shackles Springs</i>
AXLES	Solid Axle 39mm Round
HUBS/FORD	LM A-type PCD 114.3, 5 x 1/2" Studs (Stud Centre 66.6mm)
BEARINGS	Bearing A-type Inner Large LM67048 Outer Small LM11949
RIMS	NEW Sunraysia Type 14x5.5" CB 84mm PCD 114.3 (FORD)
TYRES	NEW 185R14C
CHASSIS	ALL 50x50 RHS
DRAW BAR	70x50x50x2.5mm RHS V-type, with spare wheel holder
SAFETY CHAIN	8mm Rated chain 450mm Long
LIGHTS	LED Multi volt 12-24v, Side Clearance Lights 5ft only 7-Pin plug

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES INCLUDE GST</u>			
	6x4	7x4	7x5	Trailer	6x4	7x4	7x5
SIDE HEIGHT	350	350	350	TRAILER			
FLOOR HEIGHT	530	530	530	Spare			
OVERAL HEIGHT	880	880	880	J/wheel			
INSIDE LENGTH	1820	2130	2130	Rego			
INSIDE WIDTH	1220	1220	1520	Cage			
DRAWBAR LENGTH	1230	1230	1320	Ramp			
OVERAL LENGTH	3100	3410	3500	H/frame			
OVERAL WIDTH	1730	1730	2030				
LOAD RATING KG	750	750	750				
ATM KG	250	267	293				
PAYLOAD KG	500	483	457	Total			

Contact _____

NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION