



12 Sherriffs Rd West
Lonsdale, SA 5160
Factory & Sales
P: (08) 8326 5041
F: (08) 8326 7128
www.modertrailers.com.au

1 Levels Court
Pooraka, SA 5095
Sales
P: (08) 8262 2562
F: (08) 8260 7366
E: sales@modertrailers.com.au

TRAY TOP TRAILERS 4500 KG AUSTRALIAN MADE

Tray Top trailer will save you time and money with minimal operating effort. These trailers are suitable for the home handy man, tradesman or professional workingman easy loading and unloading. Tray top trailers are available in standard sizes with or without sides. Home with Galvanised steel or Painted Black Steel. You can request a size shape or colour suitable for your special requirements.

STANDARD FEATURES

- 3mm Checker plate floor
- Spring handles to secure the tailgates
- Full length Side tie rails
- Front Head Board 900mm High
- V-type draw bar RHS square tube
- Spare wheel holder across draw bar
- Lockable plunger coupling
- Plug holder welded to the draw bar
- Safety Chain 10mm T Grade
- Lights in Back Channel
- ADR approved lights and reflectors
- Mudflaps to comply with AUS standards
- Rims New 16" Sunraysia
- New LT235/8516 1400kg Tyres
- Undercoat Vinyl Etch Primer Grey
- Paint Quality enamel



SPECIFICATIONS

FLOOR 3mm	Checker Plate
SIDES DROP DOWN & BACK	NO DROP SIDES
CHASSIS	100X100X3MM & 125X75X3MM Main Runner
DRAW BAR	125x75x4mm RHS V-type, with spare wheel holder
FRONT HEAD BOARD	900MM High with Tie Rail
SIDE TIE RAILS	Full Length Side Tie Rails 27x2mm Pipe Round
COUPLING	Ring Coupling 50mm - 5000kg Coupling Plate
SUSPENSION	Load Sharing Rocker Rollers Springs 16" Wheels 4500kg
AXLES	63mm Square Solid 3000kg each axle
BRAKES	ELECTRIC BRAKES BOTH AXLES WITH BRAKE AWAY UNIT
HUBS/Land Cruiser	6-Stud 12" Electric Drum
BEARINGS	HR32011 inner and LM29710/49 outer 3000kg per pair
RIMS	16" 6-Stud L/C White Steel Rim LT235/85R16 1400kg
TYRES	NEW LT235/85R16 1400kg
SAFETY CHAIN	2x 10mm T Grade

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES INCLUDE GST</u>			
	12x6	14x7	14x8		12x6	14x7	14x8
SIDE HEIGHT	-	-	-	TRAILER			
FLOOR HEIGHT	940	940	940	Spare			
OVERAL HEIGHT	1840	1840	1840	J/wheel			
INSIDE LENGTH	3600	4200	4200	Rego			
INSIDE WIDTH	1800	2100	2400	Cage			
DRAWBAR	170	1700	1700	Ramp			
OVERAL LENGTH	5300	4550	4550	H/frame			
OVERAL WIDTH	1800	2100	2400	Sides			
LOAD RATING KG	4500	4500	4500				
ATM KG	1030	1270	1300				
PAYLOAD KG	3470	3230	3200	Total			

Contract _____

NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION