



12 Sherriffs Rd West
Lonsdale, SA 5160
Factory & Sales
P: (08) 8326 5041
F: (08) 8326 7128
www.moderntailers.com.au

1 Levels Court
Pooraka, SA 5095
Sales
P: (08) 8262 2562
F: (08) 8260 7366
E: sales@moderntailers.com.au

TRAY TOP TRAILERS BRAKED SINGLE AXLE 1400KGAUSTRALIAN MADE (NO SIDE)

Tipper trailer will save you time and money with minimal operating effort. These trailers are suitable for the home handy man, tradesman or professional workingman easy loading and unloading. Tray top trailers are available in standard sizes with or without sides. Home with Galvanised steel or Painted Black Steel. You can request a size shape or colour suitable for your special requirements.

STANDARD FEATURES:

- Checker plate floor
- No Sides
- Full length Side tie rails
- V-type draw bar RHS square tube
- Spare wheel holder across draw bar
- Lockable plunger coupling
- Safety Chain 10mm Rated
- Light Protectors on Back Lights
- ADR approved lights and reflectors
- Mudflaps to comply with AUS standards
- Rims New 14"5.5" Sunraysia
- New 185C 14" Tyres
- Plug holder welded to the draw bar
- Paint Quality enamel



SPECIFICATIONS

FLOOR	2.1mm Rolled Checker
CHASSIS	50X50X2.5MM & 100X50X3MM Main Runner
DRAW BAR	100x50x3mm RHS V-type, with spare wheel holder
FRONT HEAD BOARD	No Head Board
SIDE TIE RAILS	Full Length Side Tie Rails 27x2mm Pipe Round
COUPLING	50mm Mechanical over Ride Plunger Type / Hand Brake
SUSPENSION	Slipper Springs 7 Leaf 1400kg Capacity
AXLES	45mm Square Solid
BRAKES	Mechanical Disc/Galvanised Calliper's True Cable Hand Brake
HUBS/FORD	14" 5-Stud Hubs
BEARINGS	68149/10 inner and 12749/10 outer
RIMS	NEW Sunraysia Type 14x5.5" CB 84mm PCD 114.3 (FORD)
TYRES	NEW 185R14C LIGHT TRUCK 850KG
SAFETY CHAIN	1x13mm Rated chain 450mm Long

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES INCLUDE GST</u>			
	7x5	7x6	8x6		7x5	7x6	8x6
SIDE HEIGHT	nil	nil	nil	TRAILER			
FLOOR HEIGHT	740	740	740	Spare			
OVERAL HEIGHT				J/wheel			
INSIDE LENGTH	2100	2100	2400	Rego			
INSIDE WIDTH	1500	1800	1800	Cage			
DRAWBAR	1500	1500	1500	Ramp			
OVERAL LENGTH	3300	3300	3600	H/frame			
OVERAL WIDTH	1800	1800	1800				
LOAD RATING KG	1400	1400	1400				
ATM KG	370	400	430				
PAYLOAD KG	1030	1000	970	Total			

Contract _____

NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION