

## **BASIC CAR CARRIER TANDEM**

### **2000KG Australian Made**

These Basic Car Carriers are manufactured to be Light Weight but also Strong enough to carrier a 1360 kg car will save you time and money with minimal operating effort. These Car Carriers are suitable for moving all Cars under 1360kg. Basic car carriers can also be made to carrier up to 3200kg or more Car Carriers can be made with a Beaver tail on back and also Tilting Drawbar, Just ask our friendly sales team. Please note the winch is extra.

#### **EXTRA FEATURES INCLUDED**

- **C/plate Runners 600mm Wide**
- **Checker Plate Ramps 2 off 300mm wide set into Back of Trailer**
- **Full Length Side Rails**
- **Top Coated in Our Standard Colours**

#### **STANDARD FEATURES**

- **Rolled C/Plate Runners**
- **Front Wheel Stops**
- **Mudguards checker plate 230mm high Allowing for car doors to open**
- **Mudflaps and all electrical complying with Australian standards**
- **New wheels (NOTE: NOT SECOND HAND)**



## SPECIFICATIONS

<b>FLOOR</b>	<b>600mm wide 2.1mm Checker Plate Runners</b>
<b>MUDGARD</b>	<b>2.1mm Checker Plate, 250mm Wide 4 Fold</b>
<b>CHASSIS</b>	<b>75x50 and 50x50 RHS</b>
<b>DRAW BAR</b>	<b>100x50x3mm RHS Welded Back to Front Springs hangers, spare wheel holder and Plug Holder with 2 Off 8mm Rated chain 450mm Long</b>
<b>SUSPENSION</b>	<b>Slipper spring</b>
<b>AXLES</b>	<b>Axles 40mm Square Solid</b>
<b>BRAKES</b>	<b>Mechanical Disc/Galvanised Calliper's True Cable Hand Brake</b>
<b>HUBS/FORD</b>	<b>5 Stud Ford</b>
<b>BEARINGS</b>	<b>Bearing A-type Inner Large LM67048 Outer Small LM11949</b>
<b>RIMS</b>	<b>NEW Sunraysia Type 14x5.5" CB 84mm PCD 114.3 (FORD)</b>
<b>TYRES</b>	<b>NEW 185R14C</b>
<b>LED Multi volt 12-24</b>	<b>Lights LED, ADR approved lights (Protected) front and side reflectors Comes with 7 pin round plug</b>

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES INCLUDE GST</u>			
	14x6'3	16x6'3	16x6'6	Trailer	14x6'3	16x6'3	16x6'6
<b>MUDGUARD HEIGHT</b>	230	230	230	<b>TRAILER</b>			
<b>FLOOR HEIGHT</b>	520	52	520	<b>Spare</b>			
<b>OVERAL HEIGHT</b>	750	750	750	<b>J/wheel</b>			
<b>INSIDE LENGTH</b>	4200	4800	4800	<b>Rego</b>			
<b>INSIDE WIDTH</b>	1900	1900	2000	<b>Cage</b>			
<b>DRAWBAR LENGTH</b>	1650	1650	1650	<b>Ramp</b>			
<b>OVERAL LENGTH</b>	5850	6450	6450	<b>H/frame</b>			
<b>OVERAL WIDTH</b>	2400	2500	2500	<b>Winch</b>			
<b>LOAD RATING KG</b>	2000	2000	2000	<b>Beaver tail</b>			
<b>ATM KG</b>	608	637	641	<b>3200kg</b>			
<b>PAYLOAD KG</b>	1392	1363	1359	<b>Total</b>			

**Contract** \_\_\_\_\_

**NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION**