

GALVANISED ROLLED BODY TANDEM 3200kg

EXTRA FEATURES INCLUDED

- **ROCKER ROLLER SPRINGS**
- **TUBE HOLDER IN EACH CORNER**
- **FULL LENGH SIDE TIE RAILS**
- **FULLY HOT DIPPED GAVANISED**

STANDARD FEATURES

- **Rolled C/Plate floor with 350mm High Side**
- **Front & rear opening tailgates tie rails**
- **C/Plate Tailgates & Mudguards**
- **Swing handles to secure the tailgates**
- **V- type draw bar made from square RHS tube**
- **Spare Wheel Holder on Draw Bar**
- **Lockable plunger coupling**
- **LED ADR approved lights and reflectors**
- **Light protectors**
- **Mudflaps to comply with Australian standards**
- **New wheels (NOTE NOT SECOND HAND)**
- **Plug holder fitted on draw bar**
- **Electric brake both axles /Cable hand brake fitted**
- **Tube holders in each corner for fitting cage or H/frame**



SPECIFICATIONS

BODY/FLOOR	350MM Sides 2 piece 2.1mm Rolled Checker Plate Tub
TAILGATES	2.1mm Folded Checker Plate, with tie rails
MUDGARD	2.1mm Checker Plate, 250mm Wide 4 Fold
DEFLECTION RAILS	50x50 Angle on each side
SIDE TIE RAILS	27x2mm Pipe Round Full Length (extra reinforced)
COUPLING	50mm Electric 3500kg / Hand Brake
SUSPENSION	Rocker Roller Load Sharing Springs
AXLES/BRAKES	45mm Square Solid/
BRAKES/ ELECTRIC	On Both Axles with Brake Away Unit True Cable Hand Brake
HUBS/FORD ELECTRIC	14" 5-Stub 10" Electric Drum SL B-type PCD 114.3, 5 x 1/2" Studs
BEARINGS	B-type Inner large L68149 / B-type outer small LM12749
RIMS	NEW Sunraysia Type 14x5.5" CB 84mm PCD 114.3 (FORD)
TYRES/8 PLY	185R14C 8PLY Radial BRAND NEW WHEEL 850KG CAPACITY
CHASSIS	ALL 50x50 RHS
DRAW BAR	125x75x3mm RHS V-type, with spare wheel holder
SAFETY CHAIN	2x13mm Rated chain 450mm Long
LIGHTS	LED Multi volt 12-24v, With Side Clearance Lights 7-Pin plug

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES INCLUDE GST</u>			
	8x5	10x5	10x6	Trailer	8x5	10x5	10x6
SIDE HEIGHT	350	350	350	TRAILER			
FLOOR HEIGHT	530	530	530	Spare			
OVERAL HEIGHT	880	880	880	J/wheel			
INSIDE LENGTH	2440	3050	3050	Rego			
INSIDE WIDTH	1520	1520	1520	Cage			
DRAWBAR LENGTH	1650	1650	1650	Ramp			
OVERAL LENGTH	4140	4750	4750	H/frame			
OVERAL WIDTH	2030	2030	2030				
LOAD RATING KG	3200	3200	3200				
ATM KG	560	600	680				
PAYLOAD KG	2640	2600	2520	Total			

Contract _____

NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION