
INDUSTRIAL ROLLED BODY TANDEM 3200 KG **Land cruiser Wheels**

EXTRA FEATURES INCLUDED

- **ROCKER ROLLER SPRINGS**
- **FULL LENGTH SIDE TIE RAILS & DEFLECTION RAILS**
- **PAINTED IN MODERN STANDARD COLOURS**
- **ELECTRIC BRAKES BOTH AXLES WITH BRAKE AWAY UNIT**

STANDARD FEATURES

- **Rolled C/Plate floor with 350mm High Side**
- **Front & rear opening tailgates with tie rails**
- **C/Plate Tailgates & Mudguards**
- **Swing handles to secure the tailgates**
- **V- type draw bar made from square RHS tube**
- **Spare Wheel Holder on Draw Bar**
- **Lockable plunger coupling**
- **LED ADR approved lights and reflectors**
- **Light protectors**
- **Mudflaps to comply with Australian standards**
- **New wheels (NOTE NOT SECOND HAND)**
- **Plug holder fitted on draw bar**
- **Brakes Both Axles with Brake Away Unit /Cable hand brake fitted**



SPECIFICATIONS

BODY/FLOOR	350MM Sides 2 piece 2.1mm Rolled Checker Plate Tub
TAILGATES	Front & Back 2.1mm Folded Checker Plate, with tie rails
MUDGARD	2.1mm Checker Plate, 250mm Wide 4 Fold
DEFLECTION RAILS	50x50 Angle on each side
SIDE TIE RAILS	Full Length 27x2mm Pipe Round
COUPLING	50mm Electric 3500kg / Hand Brake
SUSPENSION	Spring Rocker Roller 7-leaf H/Duty Set 3500kg 16" wheels
AXLES	45mm Square Solid
BRAKES/ELECTRIC	10" Drum Both Axles with Brake Away Unit True Cable Hand Brake
HUBS/FORD	16" 6-Stud 10" Electric Drum Or 5 Stud
BEARINGS	B-type Inner large L68149 / B-type outer small LM12749
RIMS	NEW Sunraysia Type LT235/85R16
TYRES/16"	LT235/70R16 950kg (Also available in 1400kg)
CHASSIS	ALL 75x50 RHS
DRAW BAR	125x75x3mm RHS V-type, with spare wheel holder 1650mm from front
SAFETY CHAIN	2x13mm Rated chain 450mm Long
LIGHTS	LED Multi volt 12-24v, With Side Clearance Lights 7-Pin plug

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES</u>			
	8x5	10x5	10x6	Trailer	8x5	10x5	10x6
SIDE HEIGHT	350	3050	350	TRAILER			
FLOOR HEIGHT	540	540	540	Spare			
OVERAL HEIGHT	890	890	890	J/wheel/JW8			
INSIDE LENGTH	2400	3000	3000	Rego 12 MTH			
INSIDE WIDTH	1520	1520	1820	Cage			
DRAWBAR/LENGTH	1650	1650	1650	Ramp			
OVERAL LENGTH	4100	4700	4700	H/frame			
OVERAL WIDTH	2030	2030	2330				
LOAD RATING KG	3200	3200	3200				
ATM KG	645	700	750				
PAYLOAD KG	2555	2500	2450	Total			

Contact _____

NOTE SPECIFICATION CAN CHANGE WITHOUT NOTIFICATION