

# ***OFF ROAD MODEL***

## ***Australian Made***

### **STANDARD FEATURES**

- **Rolled C/Plate floor and body 450mm High Side**
- **Off Road Shackle Springs with Heavy Duty Axle**
- **C/Plate pans in each corner/ C/Plate Mudguards**
- **2 jerry can holders fitted in front for both sides**
- **Checker Plate front and rear drop down tailgates**
- **Side Tie Rails and on both tailgates**
- **Swing handles to secure gates**
- **Spare Wheel Holder on Draw Bar**
- **50mm lockable plunger coupling**
- **LED Lights ADR approved with Front & side reflectors**
- **Light guard protectors on back Lights**
- **Mudflaps to comply with Australian standards**
- **New Rims & Tyres (NOTE NOT SECOND HAND)**
- **V-type draw bar RHS square tube**
- **Plug holder welded to the draw bar**



## SPECIFICATIONS

<b>BODY/FLOOR</b>	<b>450MM Sides 2 piece 2.1mm Rolled Checker Plate Tub</b>
<b>TAILGATES</b>	<b>2.1mm Folded Checker Plate, with tie rails</b>
<b>MUDGARD</b>	<b>2.1mm Checker Plate, 275mm Wide</b>
<b>SIDE TIE RAILS</b>	<b>27x2mm &amp; Checker plate pans on each side</b>
<b>COUPLING</b>	<b>50mm Lockable Plunger</b>
<b>SUSPENSION</b>	<b>Spring Shackle 60x7x7-Leaf 1450kg per Pair</b>
<b>AXLES</b>	<b>Axle 45mm Heavy Duty Square Slime Line</b>
<b>HUBS</b>	<b>L/C 6-Stud PCD 139.7 1/2" Studs SL B-Type Bearings 80'S</b>
<b>BEARINGS</b>	<b>SL B-Type: Inner Large LM681489, Outer Small LM12749</b>
<b>RIMS/NEW</b>	<b>16*6" 6 on 5.5" White Spoke Steel Rim CB 84mm PCD 139.7</b>
<b>TYRES/NEW</b>	<b>LT235/70R16 950kg</b>
<b>CHASSIS/STRUTS</b>	<b>All 50x50 RHS</b>
<b>DRAW BAR</b>	<b>100x50x3 mm RHS V-type, with spare wheel holder</b>
<b>SAFETY CHAIN</b>	<b>8mm Rated chain 450mm Long</b>
<b>LIGHTS /LED</b>	<b>Multi volt 12-24v,7-Pin plug/Side Clearance Lights 7x5 Only</b>

<u>TRAILER DIMENSIONS</u>				<u>TRAILER PRICES INCLUDE GST</u>			
	6X4	7X4	7X5	Trailer	6X4	7X4	7X5
<b>SIDE HEIGHT</b>	450	450	450	<b>TRAILER</b>			
<b>FLOOR HEIGHT</b>	565	565	565	<b>Spare</b>			
<b>OVERAL HEIGHT</b>	1015	1015	1015	<b>J/wheel</b>			
<b>INSIDE LENGTH</b>	1800	2100	2100	<b>Rego 12 MTH</b>			
<b>INSIDE WIDTH</b>	1220	1220	1520	<b>Cage</b>			
<b>DRAWBAR</b>	1400	1400	1400	<b>Ramp</b>			
<b>OVERAL LENGTH</b>	3250	3550	3350	<b>H/frame</b>			
<b>OVERAL WIDTH</b>	1770	1770	2070	<b>Brakes</b>			
<b>LOAD RATING KG</b>	750	750	750				
<b>ATM KG</b>	362	387	418				
<b>PAYLOAD KG</b>	388	363	332	<b>Total</b>			

**Contact** \_\_\_\_\_

**NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION**