
COMMERCIAL ROLLED BODY TANDEM 2000KG

This Trailer is Australian Made

EXTRA FEATURES INCLUDED

- **ROCKER ROLLER SPRINGS/ HEAVY CAST HANGER**
- **FULL LENGH SIDE TIE RAILS/DEFLECTION RAILS**
- **UNDERCOATED & SEALED ON OUTSIDE**
- **TOP COATED IN OUR STANDARD COLOURS**
- **45mm Solid Square Slim Line Axles Heavy Duty Bearing**

STANDARD FEATURES

- **Rolled Checker Plate floor with 350mm High Side**
- **Draw bar Steel RHS tube For More Strength– Plug Holder**
- **Mechanical disk brakes /Cable hand brake fitted**
- **Coupling 50mm over ride mechanical lockable & adjustable**
- **Tube holders in each corner for extra strength & fitting cage**
- **Front & rear opening Checker Plate tailgates with tie rails**
- **Swing handles to secure the tailgates**
- **Checker Plate Double Folded Mudguards with skid rails**
- **Spare wheel holder on draw bar and plug holder**
- **LED ADR approved lights protected and reflectors**
- **Rubber Mudflaps**
- **Brand New 14” Wheels (NOTE NOT SECOND HAND)**



SPECIFICATIONS

BODY/FLOOR	350MM Sides 2 piece 2.1mm Rolled Checker Plate Tub 300mm High Sides
CHASSIS	ALL 50x50 Painted RHS
DRAW BAR	100x50x3mm Painted RHS with spare wheel holder
SAFETY CHAIN	2x10mm Rated chain 650mm Long
TAILGATES	2.1mm Folded Checker Plate, with tie rails
MUDGUARD	2.1mm Checker Plate, 250mm Wide 4 Fold
DEFLECTION RAILS	50x50 Angle on each side
SIDE TIE RAILS	Full Length 27x2mm Pipe Round
COUPLING	50mm Mechanical over Ride Plunger Type / Hand Brake
SUSPENSION	Rocker Roller Load Sharing Springs
AXLES	45mm Square Solid Slim Line
BRAKES	Mechanical Disc/Galvanised Calliper's True Cable Hand Brake
HUBS/FORD	SL B-type PCD 114.3, 5 x 1/2" Studs (Stud Centre 66.6mm)
BEARINGS	Bearing B-type Inner Large L68149 / B-type outer Small LM12749
RIMS	NEW Sunraysia Type 14x5.5" CB 84mm PCD 114.3 (FORD)
TYRES	Brand New 185R14C LIGHT TRUCK 850KG
LIGHTS	LED Multi volt 12-24v, With Side Clearance Lights 7-Pin plug

TRAILER DIMENSIONS				TRAILER PRICES			
	8x5	10x5	10x6	Trailer	8x5	10x5	10x6
SIDE HEIGHT	350	350	350	Trailer Price			
FLOOR HEIGHT	540	540	540	Spare			
OVERAL HEIGHT	890	890	890	J/wheel/JW8			
INSIDE LENGTH	2400	3000	3000	Rego 12 MTH			
INSIDE WIDTH	1520	1520	1820	Cage			
DRAWBAR LENGTH	1650	1650	1650	Ramp			
OVERAL LENGTH	4100	4700	4700	H/frame			
OVERAL WIDTH	2030	2030	2330				
LOAD RATING KG	2000	2000	2000				
ATM KG	530	575	610				
PAYLOAD KG	1470	1425	1390	Total			

Contract _____

NOTE SPECIFICATIONS CAN CHANGE WITHOUT NOTIFICATION